Pg-28 (Back Cover)
Pg-1 (Cover)





Head Office & Experience Centre:
No. 693, M.N.S. Arcade, East Facing, 1st & 3rd Floor,
Dr. Rajkumar Road, 6th Block, Rajajinagar,
Bengaluru - 560 010. | Ph.: 080-23101277
Cell: +91 99801 11468, 97404 22863


E-mail: vtechbuildingsystems@gmail.com
Web: www.vtechwindows.com / www.vtechfacade.com

Works:


UNIT-1:

No. 162/1, N.S.R. Complex, East Facing, Beside ICTS, Kalenahalli, Shivakote, Hesaraghatta, Bengaluru - 560 089. UNIT-2:

No. 150, East Facing, Beside ICTS, Kalenahalli, Shivakote, Hesaraghatta, Bengaluru - 560 089.



Page-2 Page-3



OVER VIEW

V-Tech Building Systems Private Limited, established in 2012, specializes in manufacturing uPVC windows and doors, having successfully completed numerous projects with a team of over 150 professionals.

Our state-of-art manufacturing facility is capable of producing up to 100 windows per day, adhering to stringent quality standards.

Our commitment to delivering top-quality products on time has been the cornerstone of our success. As our business evolved, we partnered with Fundermax, an industry leader in high-pressure laminates (HPL) for cladding and Wesmarc for premium rebated engineered wood doors.

Recognizing the market's growing demand for System Aluminium solutions, V-Tech, backed by extensive experience in façade and fenestration, has ventured into the production of high-quality, sleek aluminium windows and doors. VATAYANAM with a dedicated facility and a team of experienced professionals, we are committed to delivering the finest System Aluminium windows in the industry.

VATAYANAM is continuing companies legacy of excellency in the facade and fenestration industry.


VATAYANAM

VATAYANAM is a vibrant and forward-thinking company, specializing in premium aluminium windows and doors manufacturing. With a focus on innovation, it leverages the latest advancements in façade and fenestration technology to provide high-performance solutions for modern architectural needs.

Despite being a young company, VATAYANAM operates with a commitment to excellence, ensuring no compromise in the quality and functionality of its products. The company's offerings are designed to deliver a comprehensive range of benefits that meet the highest industry standards. These include superior sound insulation, which significantly reduces external noise, making it ideal for urban environments.


VATAYANAM's products are engineered to withstand high wind loads, ensuring durability and safety even in harsh weather conditions. They are also water-tight, preventing leaks and ensuring long-lasting performance. With high air permeability, the products contribute to energy efficiency by maintaining optimal indoor temperatures. Additionally, they are impact-resistant, adding another layer of protection and durability.

What sets VATAYANAM apart is its ability to blend these functional advantages with cutting-edge aesthetics. The result is sleek, modern window and door systems that not only perform exceptionally but also enhance the visual appeal of any building. This fusion of performance and design is the hallmark of VATAYANAM's approach.




V-TECH BUILDING SYSTEMS PVT. LTD.® 03

Page-4 Page-5





WINDOWS BREATHE LIFE INTO SPACES, FILLING THEM WITH LIGHT AND DREAMS.







TECHNICAL CHARACTERISTICS

Window Height (Max) 2300mm (up to 7.5ft)

Sash Height & Width 62mm / 25mm

- Interlocking

 Slim Interlock 20mm
- Without Slim Interlock 65mm

Track Option

- 2 Track 3 Track
- 4 Track

Track Depth

- 2 Track Top/Bottom 28mm/72mm
- 2 Track Vertical 13mm/76mm
- 3 Track Top/Bottom 28mm/112mm
- 3 Track Vertical 13mm/114mm
- 4 Track Top/Bottom 28mm/145mm
- 4 Track Vertical 13mm/149mm

Glass Range


- Single Glass Sash 5 to 8mmDouble Glass Sash Upto 18mm

Corner Joint


- Track Joint 90 Degree
- Sash Joint 45 DegreeSash Joint 90 Degree
- Slim Interlock 90 Degree

RollerFix Single Roller
Fix Double Roller
Adjustable Double Roller

Locking OptionsSingle Point & Multipoint











The "Ruby" series from Vatayanam offers very slim aluminium window systems that maintain a sleek aesthetic while being robust in functionality, ensuring both style and durability.



V-TECH BUILDING SYSTEMS PVT. LTD.® 07





DOORS INVITE THE **SOUL** OF A **SPACE** TO EMBRACE THE OUTSIDE WORLD.

V-TECH BUILDING SYSTEMS PVT. LTD. 08





V-TECH BUILDING SYSTEMS PVT. LTD.® 09

The "Sapphire" series from Vatayanam offers a slim intermediate design, making it a preferred choice for those who seek a balance between strength

and a sleek, slim profile.

TECHNICAL CHARACTERISTICS

Window Height (Max) 2700mm (up to 9ft)

Sash Height & Width

65mm / 29mm

Interlocking

- Slim Interlock 18mm
- Slim Interlock 22mm
- Slim Interlock 28mm
- Without Slim Interlock 71mm

Track Option

- 2 Track3 Track
- 4 Track

Track Depth

- 2 Track Top/Bottom 27.3mm/72mm
- 2 Track Vertical 13mm/76mm
- 3 Track Top/Bottom 28mm/109mm
- 3 Track Vertical 13mm/114mm
- 4 Track Top/Bottom 28mm/145mm
- 4 Track Vertical 13mm/149mm

Corner Opening

Possible

Glass Range

- Single Glass Sash 5 to 8mm
- Laminated Glass Sash 11 to 15mm
- Double Glass Sash Upto 22mm

Corner Joint

- Track Joint 90 Degree
- Sash Joint 45 Degree
- Slim Interlock 90 Degree


Roller

Fix Single Roller Fix Double Roller Adjustable Double Roller

Locking OptionsSingle Point & Multipoint

KEY FEATURES

- European design, 29mm Slim Series
- Glazing from 5mm to 24mm
- Smooth & Effortless in Movement
- Automatic, Manual Concealed & Multipoint Lock System
- Provision for Insect Screen
- Reinforced Profile Available in Larger Opening
- Design for Mid to Large Size Shutter Sliding
- Bug & Bugler Proof Windows
- Slim Interlock Shutter Available for Single Glass & Double Glass Sliding














Page-10 Page-11





The "Pearl" series from Vatayanam offers architects the flexibility to overcome size limitations in window schedules, allowing for greater design freedom without compromising on sleekness or durability.

KEY FEATURES

- European design, 35mm Slim Series
- Window Height 3660mm (max)
- Glazing from 5mm to 24mm
- Smooth & Effortless in Movement
- Automatic, Manual Concealed & Multipoint
- Provision for Insect Screen
- Reinforced Profile Available in Larger Opening
- Design for Mid to Large Size Shutter Sliding
- Bug & Bugler Proof Windows
- Slim Interlock Shutter Available for Single Glass & Double Glass Sliding









LARGE DOORS INVITE THE MAJESTY OF THE OUTSIDE WORLD, BRIDGING VAST **SPACES**.



TECHNICAL CHARACTERISTICS

Window Height (Max) 3660mm (up to 12ft)

Sash Height & Width

59mm / 35mm

- Interlocking Slim Interlock 27mm
- Double Interlock

Track Option

- 2 Track
- 3 Track

Track Depth

- 2 Track Top/Bottom 31mm/95mm
- 2 Track Vertical 23mm/100mm
- 3 Track Top/Bottom 31mm/145mm
- 3 Track Vertical 25mm/150mm

Centre Opening

Possible

- Glass RangeSingle Glass Sash 6 to 13.5mmLaminated Glass Sash 12 to 14mm
- Double Glass Sash Upto 24mm


Corner Joint


- Track Joint 90 Degree
- Sash Joint 90 Degree .Slim Interlock 90 Degree

Roller

Fix Single Roller Fix Double Roller Adjustable Double Roller

Locking OptionsSingle Point & Multipoint





The "Emerald" series from Vatayanam is a high-end offering designed for elite architecture, featuring minimal section visibility on all sides to provide a sleek and refined aesthetic.

Emeralo VATAYANAM Sleek designs, high performance



Page-14 Page-15



Page-16 Page-17



Page-18 Page-19






APPLICATION & SECTION DETAILS

SLIDE & FOLD

SHUTTER* (mm)	HEIGHT	60
FRAME* (mm)	HEIGHT	51
FRAME WIDTH-MIN* (mm)	WIDTH	71
SIGHT LINE FRAME & SHUTTER* (mm)		90
SIGHT LINE AT FOLD* (mm)		128
THRESHOLD HEIGHT AT BOTTOM* (mm)		14

*Above data are for reference purpose only. I is advisable to take prior confirmation from the technical department.

TYPOLOGIES POSSIBLE





The "Quartz" series from Vatayanam is a top-end offering for casement windows, featuring sophisticated solutions such as sliding folding doors and tilt & turn windows, providing versatility and elegance for premium architectural designs.

KEY FEATURES

- European design, 50mm Casement Series
- Glazing from 5mm to 38mm
- Tilt & Turn system Compatible
- Molding & Square shapes clip
- Glazing from inside for security
- Corner joint & T-Joint for stronger Mechanical joinery
- Single Point to Multipoint locking systems
- Smooth & effortless in operation
- Internal & External opening system
- Design for larger opening & high wind load condition
- Bugler Proof Windows & Door system














V-TECH BUILDING SYSTEMS PVT. LTD.® 19

Page-21 Page-20 Imperial VATAYANAM
Sleek designs, high performance The "Imperial" series from Vatayanam is designed to enhance interior spaces, combining aesthetic appeal with userfriendly features to create a harmonious and functional environment. KEY FEATURES • Suitable for single or multiple sliding doors. • Suitable for sliding doors for residences, hotels, office buildings. • Profile:16 MM x 45 MM • Suitable for partition door & sliding • Can be used for single sliding door, pocket door system, telescopic sliding system, synchronized sliding system for elegant look • Glass thickness supported: 5 MM and 8 MM • Min. door width is 790mm • Max. weight capacity 60 Kg. • Both side soft close system V-TECH BUILDING SYSTEMS PVT. LTD. 20 V-TECH BUILDING SYSTEMS PVT. LTD. 21

Page-22 Page-23











The "Jett" series from Vatayanam is specifically designed for balconies, significantly enhancing the elevation and visual appeal of buildings.


CONTINUOUS RAILING TOP




Continuous Railing Top Section Number: V-10051 Weight (kg/12') : 3.200




Continuous Railing Top Section Number: V-10054 Wgigh1 (kg/12'): 4.080



Continuous Railing Top Section Number : V-10052 Weight (kg/12') : 3.400



Continuous Railing Top Section Number: V-10055 Wgight (kg/12') : 4.100




Continuous Railing Top Section Number : V-10053 Weight (kg/12') : 4.600



Continuous Railing Top Section !-.lumber: V-10056 Weight (kg/12') : 2.150

CONTINUOUS RAILING BOTTOM



Continuous Railing Bottom Section Number : V-10001 Weight (kg/12'): 15.775



Continuous Railing Bottom Section Number: V-10002 Weight (kg/12'): 9.100



Continuous Railing Bottom Section Number : V-10003 Weight (kg/12'): 14.875




Continuous Railing Bottom Section Number : V-10004 Weight (kg/12') : 6.850



Page-25 Page-24





Technical Specification

Window height (Max) 3048mm (Upto 10ft)

Sash Height & Width

73mm & SOmm

Track

Top Load System 74mmx73mm

Bottom Frame

Floor top & Concealed System

Glass Range

Single Glass 6mm to 8mm

Corner Joint

Track Joint 90 Degree Sash Joint 45 degree

Top & Bottom Double Roller

Locking System


Multi Point


Louvre Systems have tiny louvre blades and used in smaller size panels with close overlapping.


The louvre blades are assembled with the desired pitch with concealed screws within the screw ribs of the louvre profiles in specially featured vertical channels. The individual assembled panels are fitted in outer frame pockets. Each panel size ranges from 600mm. to 800mm. width to a height of 750mm to 1200mm. These assembled panels shall be fitted in series of openings of the outer frame made of rectangular box section as per individual requirements.


These are normally preferred in interiors, in the facade elements and also as per suggestions of the architects and facade consultants. The system can withstand wind pressure of 1.25kpa. However these technical parameters are to be approved by the consultants from the field depending upon individual merits.

Glazing & Louvre Systems VATAYANAM Sleek designs, high performance









The "Glazing & Louvre Systems" series from Vatayanam is designed for building elevations, creating an architectural envelope that redefines the space, giving it a distinct and transformative identity.



LOUVRE PROFILE			
Section No.	THICK mm.	Weight kg/m	
20970	1.29	0.248	
21591	2.15	0.610	
21713	1.80	0.385	



F	FRAME PROFILE		
Section No.	THICK mm.	Weight kg/m	
14144	2.00	0.767	
14070	1.47	0.781	
14013	2.00	1.054	
14029	1.20	0.643	





KEY FEATURES

- European design
- Top sliding system
- Molding & Square shapes clip
- Glazing from inside for security • Corner joint & T-Joint for stronger
- Mechanical joinery
- Single Point to Multipoint locking systems
- Smooth & effortless in operation
- Internal & External opening system
- Design for larger opening & high wind load condition
- Bugler Proof Windows & Door system












V-TECH BUILDING SYSTEMS PVT. LTD. 25

Page-26 Page-27



LETYOUR DOORS & WINDOWS EXPRESSTHIER OWNBEAUTIFUL TALE...!





